

**Makita**

# 18Vx2 Brushless Wet/Dry Dust Extraction Vacuum

DVC155LZX4



**18Vx2 18V + 18V 36V**  
**BRUSHLESS**

# Product Overview



# Product Specification Sheet



- **Redesigned housing** - minimises excess air noise to reduce operation volume
- **Large On/Off Switch** – allows for easy operation
- **Durable Container** – Durable plastic container absorbs impacts without denting or warping like metal containers
- **Dual Battery Indicator** – Indicates the remaining power in each battery
- **Variable Speed Dial** – easily adjustable suction control for optimum runtime and performance
- **15L Tank Capacity** – increased tank capacity to minimise down time between disposals
- **Removable storage box** – allows for storing extra batteries and accessories and also doubles as stabiliser
- **Rubber Bumper** – eliminates risk of damage to furniture and chairs while moving the vacuum around worksite

Max. sealed suction	11kPa
Max. air volume (m <sup>3</sup> /min)	2.1m <sup>3</sup> /min
Tank capacity	Dry: 15L / Wet: 12L
Suction power	105W
Continuous runtime BL1860B x2	40 minutes
Weight (with battery)	7.8kg
Voltage	18Vx2 (36V)

# Advantages

## Performance



18Vx2 Brushless technology provides a High suction for a range of applications

## Versatility



Variable suction control for optimum runtime & performance

## Convenience



Removable on-board storage & stabilizing leg for pipes, nozzles and batteries

## Ergonomic



Large On/Off switch for easy operation

# Our Range

	NEW – DVC155LZX4	DVC150LZ	DVC157LZX2
			
Max. sealed suction	11kPa	AC: 24kPa DC: 9kPa	11kPa
Max. air volume (m <sup>3</sup> /min)	2.1m <sup>3</sup> /min	AC: 3.6m <sup>3</sup> /min DC: 2.1m <sup>3</sup> /min	2.1m <sup>3</sup> /min
Tank capacity	Dry: 15L / Wet: 12L	Dry: 15L / Wet: 12L	15L
Suction power	105W	AC: 320W DC: 70-25W	105W
Continuous Runtime (Max) 6.0Ah	40 minutes	36 minutes	40 minutes
Weight (with battery)	7.9kg	9.6kg	8.5kg
Voltage	18Vx2(36V)	AC or 18Vx2(36V)	18Vx2(36V)

# Accessories

Standard Accessories		
	122512-4	Combination Floor Tool
	192563-1	Straight Aluminium Pipe
	192562-3	Bent Aluminum Pipe
	195434-1	38mm Hose x 2.5m
	410306-2	Crevice Nozzle
	195432-5	Plastic Tub Liner (10pk)

Optional Accessories		
	195557-5	Fleece Filter Bag (5pk)
	140248-3	Cloth Pre-Filter
	195552-5	Foam Damper
	197166-6	HEPA Filter
	195555-9	Wet Filter
	195546-0	Joint Cuff 22-38
	195548-6	Front Cuff 24

# Frequently Asked Questions

## **How do I install the HEPA filter?**

Remove the 3 x screws attaching the float cage to the bottom of the motor housing. Remove the standard pre-filter and replace with the option cloth pre-filter, foam damper & HEPA filter assembly.

## **How do I use the vacuum for wet pickup?**

Ensure the float cage and float are assembled correctly under the motor housing. Install the plastic tub liner if required and wet filter assembly (optional accessory).