

**Makita**<sup>®</sup>  
mt

**ONE RANGE  
MANY SOLUTIONS**

**INDUSTRIAL  
RELIABILITY**



**ERGONOMICALLY  
DESIGNED**



**18V  
MOBILE POWER**



**HEAVY DUTY  
POWER**



**MT SERIES  
PRODUCT RANGE**



E&OE / 5513-01

**SIMPLE SOLID POWER**

## 18V Hammer Driver Drill Kit

M8301D003



NEW

- Kit includes: 18V hammer driver drill, 2 x 2.0Ah batteries and charger
- Mechanical 2 speed gearing
- 42Nm of max. fastening torque

Standard: 2 x Li-ion Batteries (BL1820G), Charger (DC18WB), Case

Max. drilling capacities in wood	36mm
Max. drilling capacities in steel	13mm
Max. drilling capacities in masonry	13mm
No load speed	Hi: 0 - 1,400rpm Lo: 0 - 400rpm
Impact rate	Hi: 0 - 21,000ipm Lo: 0 - 6,000ipm
Max. lock torque	38Nm
Max. tightening torque	Hard: 42Nm Soft: 24Nm
Overall length	238mm
Skin weight	1.3kg
Weight (with battery)	1.7kg
Voltage	18V G-Series

## 18V Driver Drill Kit

M6301D003



NEW

- Kit includes: 18V driver drill, 2 x 2.0Ah batteries and charger
- Mechanical 2 speed gearing
- 1,400rpm no load speed for smooth performance

Standard: 2 x Li-ion Batteries (BL1820G), Charger (DC18WB), Case

Max. drilling capacities in wood	36mm
Max. drilling capacities in steel	13mm
No load speed	Hi: 0 - 1,400rpm Lo: 0 - 400rpm
Max. lock torque	38Nm
Max. tightening torque	Hard: 42Nm Soft: 24Nm
Overall length	223mm
Skin weight	1.3kg
Weight (with battery)	1.7kg
Voltage	18V G-Series

## 18V Impact Driver Kit

M6901D003



NEW

- Kit includes: 18V impact driver, 2 x 2.0Ah batteries and charger
- Variable speed trigger with forward/reverse switch
- Provides 135Nm max. torque

Standard: 2 x Li-ion Batteries (BL1820G), Charger (DC18WB), Case

Max. capacities standard bolt	M5 - M14
Max. capacities high tensile bolt	M5 - M12
No load speed	0 - 2,400rpm
Impact rate	0 - 3,000rpm
Max. tightening torque	135Nm
Drive shank	6.35mm (1/4") Hex
Overall length	173mm
Skin weight	1.1kg
Weight (with battery)	1.5kg
Voltage	18V G-Series

## 10mm (3/8") Drill

M6001B



85

Max. drilling capacities in wood	25mm
No load speed	10mm
Max. fastening torque	0 - 3,000rpm
Continuous rating input	450W
Overall length	229mm
Net weight	1.3kg
Power supply cord	2.0m

- Variable speed trigger with forward/reverse switch
- Keyed chuck for industrial reliability
- Reliable 450W\* motor
- Long life carbon brushes

\*Continuous rating input

Standard: Chuck Key (763444-2), Chuck Key Holder (418163-2)

## 10mm (3/8") Drill

M6002B



85

Max. drilling capacities in wood	25mm
Max. drilling capacities in steel	10mm
No load speed	0 - 3,000rpm
Continuous rating input	450W
Overall length	234mm
Net weight	1.3kg
Power supply cord	2.0m

- Variable speed trigger with forward/reverse switch
- Keyless chuck for easy bit change
- Reliable 450W\* motor
- Long life carbon brushes

\*Continuous rating input

Standard: None

## 6.5mm (1/4") High Speed Drill

M6501B



85

Max. drilling capacities in wood	9mm
Max. drilling capacities in steel	6.5mm
No load speed	0 - 4,500rpm
Continuous rating input	230W
Overall length	203mm
Net weight	0.95kg
Power supply cord	2.0m

- Trigger switch with variable speed dial and forward/reverse switch
- Keyed chuck for industrial reliability
- Reliable 230W\* motor
- Lightweight ergonomic design

\*Continuous rating input

Standard: Chuck Key (763449-2), Chuck Key Holder (418198-3)

## Mixing Drill

## M6600B



303

Collet size	M14
No load speed	0 - 700rpm
Continuous rating input	800W
Overall length	280mm
Net weight	3.4kg
Power supply cord	2.0m

- Variable speed trigger with forward/reverse switch
- Accepts M14 thread mixer bits
- Reliable 800W\* motor
- Ergonomic dual grip design

\*Continuous rating input  
Standard: Wrench (781010-3), Side Grip (142088-5)

## 16mm (5/8") Hammer Drill

## M8100KB



85

Max. drilling capacities in concrete	16mm
Max. drilling capacities in wood	30mm
Max. drilling capacities in steel	13mm
No load speed	0 - 3,200rpm
Impact rate	0 - 48,000ipm
Continuous rating input	710W
Overall length	296mm
Net weight	2.1kg
Power supply cord	2.0m

- Variable speed trigger with forward/reverse switch
- Keyed chuck for industrial reliability
- Reliable 710W\* motor
- Ergonomic design for maximum control

\*Continuous rating input  
Standard: Depth Gauge (21144-6), Side Grip (153503-4), Chuck Key (763441-8), Chuck Key Holder (418163-2) Case

## 16mm (5/8") Hammer Drill

## M8101KB



85

Max. drilling capacities in concrete	16mm
Max. drilling capacities in wood	30mm
Max. drilling capacities in steel	13mm
No load speed	0 - 3,200rpm
Impact rate	0 - 48,000ipm
Continuous rating input	710W
Overall length	295mm
Net weight	2.0kg
Power supply cord	2.0m

- Variable speed trigger with forward/reverse switch
- Keyless chuck for easy bit change
- Reliable 710W\* motor
- Ergonomic design for maximum control

\*Continuous rating input  
Standard: Depth Gauge (21144-6), Side Grip (153503-4), Case

## 82mm Planer

## M1901B



411

Shiplapping / Rebate	9mm
Planing width	82mm
Max. planing depth	2mm
No load speed	16,000rpm
Continuous rating input	580W
Overall length	285mm
Net weight	2.7kg
Power supply cord	2.0m

- 82mm width with up to 2.0mm depth and 9mm rebate planing capacity
- One side chip ejection
- Reliable 580W\* motor for smooth easy operation
- V-Groove base plate for chamfer cuts

\*Continuous rating input  
Standard: Guide Rule (165378-9), Wrench (782229-7), Blade Gauge (122695-0)

## 255mm (10") Compound Mitre Saw

## M2300B



500

Max. cutting capacities at 90°	75 x 130mm
Max. cutting capacities at 45° mitre	75 x 90mm
Blade diameter	255mm (10")
Bore diameter	25.4mm
No load speed	4,200rpm
Continuous rating input	1,500W
Bevel capacity	45° left
Mitre capacity	45° left - 45° right
Overall length	485mm
Net weight	14.7kg
Power supply cord	2.0m

- 75 x 130mm max. cut capacity
- 45° left and right mitre and 0° - 45° left bevel
- Reliable 1,500W\* motor
- Electric brake for added safety

\*Continuous rating input  
Standard: 255mm Saw Blade, Wrench Dust Bag, Holder Set, Vise Assembly

## 355mm (14") Cut-Off Saw

## M2401B



203

Max. cutting capacities at 90°	102 x 194mm
Max. cutting capacities at 45° mitre	115 x 103
Wheel diameter	355mm (14")
Hole diameter	25.4mm
No load speed	3,800rpm
Continuous rating input	2,000W
Overall length	500mm
Net weight	13.7kg
Power supply cord	2.0m

- Cutting capacity of 102 x 194mm, 70 x 233mm or 115mm diameter
- Adjustable guide plate with 3 settings
- Reliable 2,000W\* motor
- Ergonomic design with anti-slip grip

\*Continuous rating input  
Standard: Abrasive Cut-off Wheel, Hex Wrench

## 12.7mm (1/2") Plunge Router

M3600B



203

Collet capacity	12.7mm (1/2")
Plunge capacity	0 - 60mm
Base diameter	160 x 148mm
No load speed	22,000rpm
Continuous rating input	1,650W
Overall length	284mm
Net weight	5.5kg
Power supply cord	2.0m

- Toggle switch
- Quick release depth adjustment
- Reliable 1,650W\* motor
- Ergonomic design for user comfort and control
- Shaft lock for easy bit changes

\*Continuous rating input  
Standard: Wrench, Collet Sleeve 6.35mm (763809-8) Collet Sleeve 9.53mm (763810-3),  
Template Guide (345387-6), Straight Guide, Guide Holder (122700-3), Straight Bit

## 8mm (5/16") Router

M3601B



106

Collet capacity	8mm (5/16")
Plunge capacity	0 - 35mm
Base diameter	145 x 110mm
No load speed	27,000rpm
Continuous rating input	1,000W
Overall length	256mm
Net weight	2.7kg
Power supply cord	2.0m

- Trigger on side handle
- Easy depth adjustment
- Reliable 1,000W\* motor
- Ergonomic handle design

\*Continuous rating input  
Standard: Straight Guide (164834-6), Straight Bit, 2 x Wrench, Collet Cone 6.35mm  
(763637-1), Collet Cone 8mm (763618-5)

## 6.35mm (1/4") Laminate Trimmer

M3700B



411

Collet capacity	6.35mm (1/4")
Plunge capacity	0 - 42mm
No load speed	35,000rpm
Continuous rating input	530W
Overall length	199mm
Net weight	1.4kg
Power supply cord	2.0m

- Toggle switch
- Clear base for visible cutting
- Reliable 530W\* motor
- Narrow barrel for easy control
- Top mounted cord for easy operation

\*Continuous rating input  
Standard: 2 x Wrench, Trimmer Guide (122703-7), Straight Bit, Template Guide  
(343577-5), Collet Cone 6.35mm (763663-0)

## D-Handle Jigsaw

M4301B



64

Max. cutting capacities in wood at 90°	65mm
Max. cutting capacities in steel at 90°	6mm
Length of stroke	18mm
Strokes per minute	0 - 3,100spm
Bevel capacity	45° left - 45° right
Continuous rating input	450W
Overall length	214mm
Net weight	1.9kg
Power supply cord	2.0m

- Variable speed by trigger
- 18mm stroke with cut capacity of up to 65mm in wood and 6mm in steel
- Reliable 450W\* motor
- 3 orbital cutting settings
- Tool-less blade changes

\*Continuous rating input  
Standard: B-10 Blade (A-85628), Hex Wrench (783201-2)

## D-Handle Jigsaw

M4302B



411

Max. cutting capacities in wood at 90°	55mm
Max. cutting capacities in steel at 90°	6mm
Max. cutting capacities in aluminium at 90°	12mm
Length of stroke	26mm
Strokes per minute	0 - 3,100spm
Bevel capacity	45° left - 45° right
Continuous rating input	450W
Overall length	219mm
Net weight	2.5kg
Power supply cord	2.0m

- Variable speed control by dial and trigger
- 26mm stroke with cut capacity of up to 55mm in wood and 6mm in steel
- Reliable 450W\* motor

\*Continuous rating input  
Standard: 5 x Piece Blade Set (A-86898), 1 x No.51 Jigsaw Blade,  
1 x B-13 Jigsaw Blade, Hex Wrench (783201-2)

## 185mm (7-1/4") Circular Saw

M5802B



303

Max. cutting capacities at 90°	66mm
Max. cutting capacities at 45°	44mm
Bevel capacity	0° - 45°
Blade diameter	185mm (7 - 1/4")
Bore diameter	20mm
No load speed	4,900rpm
Continuous rating input	1,050W
Overall length	297mm
Net weight	4.0kg
Power supply cord	2.0m

- Max. cutting depth of 66mm
- Max. bevel capacity of 45°
- Reliable 1,050W\* motor
- Ergonomic design for comfort and control
- Simple locking lever for depth adjustment

\*Continuous rating input  
Standard: 185mm Blade (D-09123), Guide Rule (164095-8), Hex Wrench (783217-7)

## Recipro Saw

M4501B



303

Max. cutting capacities in wood	255mm
Max. cutting capacities in pipe	130mm
Length of stroke	28mm
Strokes per minute	0 - 2,800spm
Continuous rating input	1,010W
Overall length	457mm
Net weight	3.2kg
Power supply cord	2.0m

- 28mm stroke with cut capacity of 255mm in wood and 130mm in pipe
- Durable designed for reliable performance in harsh conditions
- Reliable 1,010W\* motor
- Large trigger for user comfort
- Tool-less blade clamp

\*Continuous rating input  
Standard: Carry Case

## 6mm (1/4") Die Grinder

M9100B



411

Max. wheel size	20mm
Collet	6.35mm (1/4")
Max. collet capacity	6.35mm (1/4")
No load speed	33,000rpm
Continuous rating input	480W
Overall length	350mm
Net weight	1.5kg
Power supply cord	2.0m

- Toggle Switch
- Aluminium barrel with stepped neck for stability while grinding
- Reliable 480W\* motor delivers smooth performance
- Anti-slip grip for better control

\*Continuous rating input  
Standard: Collet Cone (763666-4), Collet Nut (763664-8), 2x Wrench (781039-9)

## 125mm (5") Angle Grinder

M9508B



459

Wheel diameter	125mm (5")
Hole diameter	22.23mm
Spindle thread	M14 x 2
No load speed	11,000rpm
Continuous rating input	720W
Overall length	261mm
Net weight	1.9kg
Power supply cord	2.0m

- Slide switch with lock-on function
- Design for durability with dust proof construction
- Powerful 720W\* motor with excellent heat-resistance

\*Continuous rating input  
Standard: Side Grip (153489-2), Wheel Guard (123099-9), Lock Nut (224554-5), Lock Nut Wrench (782423-1)

## 125mm (5") Angle Grinder

M9511B



325

Wheel diameter	125mm (5")
Hole diameter	22.23mm
Spindle thread	M14 x 2
No load speed	11,000rpm
Continuous rating input	850W
Overall length	276mm
Net weight	2.0kg
Power supply cord	2.0m

- Slide switch with lock-on function
- Design for durability with dust proof construction
- Powerful 850W\* motor with excellent heat resistance

\*Continuous rating input  
Standard: Side Grip (153489-2), Wheel Guard (123099-9), Lock Nut (224554-5), Lock Nut Wrench (782423-1)

## 125mm (5") Angle Grinder

M9002B



303

Wheel diameter	125mm (5")
Hole diameter	22.23mm
Spindle thread	M14 x 2
No load speed	11,000rpm
Continuous rating input	1,050W
Overall length	361mm
Net weight	2.8kg
Power supply cord	2.0m

- Trigger switch for safe control
- Design for durability with dust proof construction
- Reliable 1,050W\* motor delivers high performance
- Lightweight design for easier handling

\*Continuous rating input  
Standard: Side Grip (153504-2), Wheel Guard (123099-9), Lock Nut (224554-5), Lock Nut Wrench (782423-1)

## 180mm (7") Angle Grinder

M9000B



204

Wheel diameter	180mm (7")
Hole diameter	22.23mm
Spindle thread	M14 x 2
No load speed	8,500rpm
Continuous rating input	2,000W
Overall length	466mm
Net weight	5.4kg
Power supply cord	2.0m

- Trigger switch design for safe control
- Design for durability with dust proof construction
- Reliable 2,000W\* motor delivers high performance
- Machined spiral gearing for durability

\*Continuous rating input  
Standard: Side Grip (152539-0), Wheel Guard (122890-2), Lock Nut (224543-0), Lock Nut Wrench (782407-9)

## 230mm (9") Angle Grinder

M9001B



204

Wheel diameter	230m (9")
Hole diameter	22.23mm
Spindle thread	M14 x 2
No load speed	6,600rpm
Continuous rating input	2,000W
Overall length	466mm
Net weight	5.7kg
Power supply cord	2.0m

- Trigger switch design for safe control
- Design for durability with dust proof construction
- Reliable 2,000W\* motor delivers high performance
- Machined spiral gearing for durability

\*Continuous rating input  
Standard: Side Grip (152539-0), Wheel Guard (122892-8), Lock Nut (224543-0), Lock Nut Wrench (782407-9)

## Hex Shank Demolition Hammer

M8600B



105

Shank Type	17mm Hex
Impact energy	7.2j
Impact rate	2,900ipm
Vibration	16.5m/s <sup>2</sup>
Noise	102dB
Continuous rating input	900W
Overall length	406mm
Net weight	5.4kg
Power supply cord	2.0m

- Trigger switch ergonomically designed for chiseling applications
- 16.5m/s<sup>2</sup> of vibration
- Reliable 900W\* motor delivers 7.2j\*\* of power
- High durability design

\*Continuous rating input \*\*Rating in accordance EPTA 05/2009  
Standard: Side Grip (126457-8), Case

## 22mm SDS Plus Rotary Hammer

M8700B



459

Max. drilling capacities in concrete	22mm
Max. drilling capacities in wood	32mm
Max. drilling capacities in steel	13mm
Impact energy	1.9j
No load speed	0 - 1,100rpm
Impact rate	0 - 4,350ipm
Vibration	15.5m/s <sup>2</sup>
Noise	90dB
Continuous rating input	710W
Overall length	362mm
Net weight	2.5kg
Power supply cord	2.0m

- 2-mode operation: rotation only or hammer with rotation
- 15.5m/s<sup>2</sup> of vibration
- Reliable 710W\* motor delivers 1.9j\*\* of power

\*Continuous rating input \*\*Rating in accordance EPTA 05/2009  
Standard: Depth Gauge (321144-6), Side Grip (452985-0), Case

## 26mm SDS Plus Rotary Hammer

M8701B



459

Max. drilling capacities in concrete	26mm
Max. drilling capacities in wood	32mm
Max. drilling capacities in steel	13mm
Impact energy	2.3j
No load speed	0 - 1,200rpm
Impact rate	0 - 4,500ipm
Vibration	16.5m/s <sup>2</sup>
Noise	90dB
Continuous rating input	800W
Overall length	362mm
Net weight	2.7kg
Power supply cord	2.0m

- 3-mode operation: rotation, hammer with rotation or hammer
- 16.5m/s<sup>2</sup> of vibration
- Reliable 800W\* motor delivers 2.3j\*\* of power
- High durability design

\*Continuous rating input \*\*Rating in accordance EPTA 05/2009  
Standard: Depth Gauge (321144-6), Side Grip (452985-0), Case

## 1/3 Sheet Finishing Sander

M9203B



64

Pad size	92 x 185mm
Abrasive paper size	93 x 228mm
Orbits per minute	12,000opm
Orbit diameter	2.0mm
Sanding strokes	24,000spm
Continuous rating input	190W
Overall length	252mm
Net weight	1.4kg
Power supply cord	2.0m

- On/off switch rocker switch
- Easy-to-operate large clamp
- Reliable 190W\* motor

\*Continuous rating input  
Standard: Punch Plate (451271-6), Dust Bag (143627-4)

## 125mm (5") Random Orbital Sander

M9204B



419

Pad diameter	123mm
Abrasive paper diameter	125mm
Orbits per minute	12,000opm
Orbit diameter	2.8mm
Sanding strokes	24,000spm
Continuous rating input	240W
Overall length	153mm
Net weight	1.2kg
Power supply cord	2.0m

- On/off switch rocker switch
- Hook and loop disc pad for quick disc replacement
- Reliable 240W\* motor
- Ergonomic soft palm grip for user comfort

\*Continuous rating input  
Standard: Dust Bag Assembly (161431-9)

## 100mm (4") Belt Sander

## M9400B



153

Belt size	100 x 610mm
Belt speed	380m/min
Continuous rating input	940W
Overall length	354mm
Net weight	6.2kg
Power supply cord	2.0m

- 100 x 610mm belt size
- Belt speeds of up to 380m/min
- Dependable 940W\* motor
- Unique design for flush to wall sanding

\*Continuous rating input  
Standard: Dust Bag (123328-0), Carbon Plate (424057-1)

## Blower

## M4000B



85

Air volume	1.2 - 2.9m³/min
Air speed	133 - 313km/h
No load speed	8,500 - 16,000rpm
Continuous rating input	530W
Overall length	427mm
Net weight	1.5kg
Power supply cord	0.2m

- In-line ergonomic design
- For user comfort at only 1.5kg
- Reliable 530W\* motor delivers over 300km/h air speed

\*Continuous rating input  
Standard: Nozzle (421905-5), Sash Nozzle (418919-3)

## Blower

## M4001B



303

Air volume	0 - 4.1m³/min
Air speed	0 - 327km/h
No load speed	0 - 16,000rpm
Continuous rating input	600W
Overall length	480mm
Net weight	2.0kg
Power supply cord	0.2m

- Variable speed control by dial and trigger
- Ergonomic lightweight design
- Reliable 600W\* motor delivers 327km/h air speed
- Vacuum function can be used with dust bag

\*Continuous rating input  
Standard: Nozzle Assembly (123245-4), Dust Bag (126688-9)