# 40V Max 300mm Top Handle Chainsaw UC003G



### **Product Statement**

UC003G is a lightweight, compact top handle chainsaw which provides fast cutting with chain speeds up to 24m/s and a max output wattage of 1.4kW.

The narrow 1.1mm chain creates less friction while cutting allowing for faster cutting & increased runtime compared to thicker gauge chains designed for petrol chainsaws.

UC003G is ideal for climbing, coming standard with a captive bar nut on the blade cover to eliminate the risk of losing small components while adjusting chain tension at heights. It also has a lanyard hook to clip it to the operator's harness so it remains secure while moving from cut to cut.



HEAVY DUTY BRUSHLESS

# **Product Overview**





# **Product Specifications**

HEAVY DUTY BRUSHLESS



| SPECIFICATIONS                 |               |  |
|--------------------------------|---------------|--|
| Max Output Wattage             | 1.4kW         |  |
| Chain Speed                    | 24m/s         |  |
| Bar Length                     | 300mm         |  |
| Standard Chain                 | 3/8" / 0.043" |  |
| Oil Capacity                   | 200mL         |  |
| Skin Weight<br>Excl. Bar/Chain | 2.6kg         |  |
| Voltage                        | 40V Max       |  |

- High Power 1.4kW Max output wattage comparable power to 30cc 2 Stroke chainsaws.
- **Ergonomic Handle** Ergonomically designed top handle with rubberized soft grip providing the user with greater comfort.
- Lanyard Hook Provides a secure point for tree climbers to attach the saw for convenient use and storage.
- **Variable Speed Trigger** User can control the speed of the chain by applying soft pressure to the trigger for smaller cuts.
- **Adjustable Chain Oiling** Allows the user to increase or reduce the amount of oil provided to the bar to ensure optimal lubrication for the application.
- Metal Spike Bumper Aggressive teeth provide a pivot point to work the bar through the material while providing increased grip & stability.
- Captive Bar Nut Anti fall captive bar nut allows for maintenance at heights without the risk of losing small components.
- Water Resistant IPX4 water penetration rating for use in wet weather situations.

# Advantages

#### Power



1.4kW Max output power equivalent to 30cc 2 stroke chainsaws

### Versatility



IEAVY DUTY RRUSHLES

Adjustable chain oil flow rate to suit different timber types

### Durability



IPX4 water penetration rating for use in all weather situations

### **Ergonomics**



Metal spike bumper grips into workpiece for added support and control

## Accessories



| Standard Accessories |                        |          |
|----------------------|------------------------|----------|
| Thakita              | Guide Bar 300mm        | 191G15-1 |
| Thakita              | Chain Bar Cover        | 419288-5 |
|                      | Chain                  | 191H01-8 |
|                      | Wrench 13mm /<br>16mm  | 782023-7 |
|                      | Bar & Chain Oil Vessel | -        |

| Optional Accessories |                                                                      |                      |
|----------------------|----------------------------------------------------------------------|----------------------|
| Thakita              | Sprocket Nose Bar 35cm325LP .043<br>Sprocket Nose Bar 40cm325LP .043 | 191G16-9<br>191G17-7 |
|                      | Chain Saw Chain 35cm325LP .043<br>Chain Saw Chain 40cm325LP .043     | 191H02-6<br>191H03-4 |
|                      | Chainsaw Sharpening File Set                                         | D-70954              |
|                      | 2 Piece Round File Set 4.5mm                                         | D-67371              |